


CE  ISO9001



BTW

Weighing Indicator

 Economic Solution

FEATURE

- The interface is simple and easy to operate
- Up to 1/15,000 display resolution
- High Speed 24bits AD; Display reading speed faster
- AC / DC switching function (Built-in rechargeable battery)
- Low power indication
- LCD display (Weight-6 digits); Full range tare; Auto zero tracking
- Simple counting; Gross/Net indication; Hold function
- Check mode Lo / Hi / OK with 3 selectable beeping sounds
- LED Lo / Hi / OK indication
- Selectable units: Kilogram (kg) and pound (lb)
- Easily viewing single weight / total weight within 1 button press

OPTION

- RS232: Bi-direction transmission, easy data reading or printing
- Sleeve connecting stand



▲ LED Lo / OK / Hi indication



▲ Can be connected to most types of platforms

SPECIFICATION

- Operating Temperature: 0°C ~ 40°C (32°F ~ 104°F)
- Power Source: AC 110V/220V (±10%) + DC 4V / 4Ah rechargeable battery
- Power Consumption: Approximately DC 12.95mA (Indicator + Load Cell + Display Backlight); can be used about 120 hours
- Display LCD 6 digits, Height 25mm, LED Backlight
- Indicator Dimensions: 235 x 163 x 133 mm (W x H x D)



*Specifications are subject to change without notice

BTW

Weighing Indicator

 Economic Solution