

COMPASS™CX SERIES

Portable Scales



Energy-Efficient Portable Scale Suitable for Workplace and In-the-Field Weighing

Designed with energy efficiency in mind, the Compass CX series offers a battery life of up to **1,000 continuous hours**, allowing for uninterrupted operation. Featuring a slim, stackable and light-weight design, the CX fits ideally in lab, industrial, education, and even household settings. The streamlined two-button operation means that the balance can be operated easily, and large backlit LCD display enables easy viewing of weighing results.

Standard Features:

- Alkaline batteries provide up to **1,000 hours of continuous use**, making for energy efficient weighing in the workplace, classroom, etc.
- Large backlit display increases readability in low-light conditions and makes it easier to view results from a distance.
- Slim, space-saving design allows for stackable storage for up to four scales.

COMPASS™CX SERIES Portable Scales

Model	CX221	CX621	CX1201	CX2200	CX5200	
Capacity (g)	220	620	1200	2200	5200	
Readability (g)	0.1				1	
Span Calibration Mass (Not Included)	200 g	500 g	1 kg 2 kg		2 kg	
Stabilization Time(s)	1.5		1	1.5		
Construction	ABS housing and stainless steel pan					
Calibration	User-selectable external span / Digital with external weight					
Tare Range	Full capacity by subtraction					
Weighing Units*	g, N, oz, Ib:oz					
Application Modes	Weighing					
Power Requirement	3 AA batteries (included) or AC adapter (not included)					
Typical Battery Life	1,000 hours					
Display Type	Liquid crystal display (LCD) with backlight					
Display Size	18 mm					
Pan Size (W \times D)	128 × 142 mm					
Balance Dimensions (W \times D \times H)	135 × 201 × 41 mm					
Shipping Dimensions (W \times D \times H)	170 × 235 × 55 mm					
Net Weight	0.5 kg					
Shipping Weight	0.7 kg					

^{*}Availability is dependent on model and region.

Other Standard Features and Equipment

ABS housing, slip-resistant feet, stability indicator, mechanical and software overload/underload protection, low battery indicator, auto shut-off


Compliance

- Product Safety: IEC/EN 61010-1
- Electromagnetic Compatibility: IEC/EN 61326-1 Class B, Basic environments; FCC Part 15 Class B; Canada ICES-003 Class B
- Compliance Marks: CE; RCM

Accessories

Carrying Case	30467763
Bowl, 1050 mL	80850075
Adapter, 5V 1A, with US plug	30330714
Adapter, 5V 1A, with AU plug	30333865
Adapter, 5V 1A, with EU plug	30333866
Adapter, 5V 1A, with UK plug	30333867
Adapter, 5V 1A, with KR plug	30333868

Dimensions



OHAUS Asia/Pacific Headquarters

7F, Block 33, 680 Guiping Road Shanghai 200233

e-mail: APmarketing@ohaus.com Tel: +86 21 64855408

www.ohaus.com

The management system governing the manufacture of this product is ISO 9001:2015 certified.

30385205



80775687_B 20190719 © Copyright OHAUS Corporation