



WE WEIGH THE WORLD

www.globalcas.com

ED-C SERIES COUNTING E-SCALE

ED-C_{series}



Set the upper and lower limits freely
Count the weight and check the alarm



LARGE BACKLIT
SCREEN



MORE ACCURATE
COUNTINGWEIGHING



HIGH STRENGTH
ABS NEW MATERIAL



MULTI-CAPACITY
WEIGHING



SUPER
ENDURANCE

CAS

ED-C

SERIES COUNTING LABEL SCALE

TOTAL WEIGHING SOLUTION™



FUNCTION SUMMARY

- High definition large display
- Free conversion between weight and count windows
- Automatic error message indication
- 24 Bit A/D converter
- Resistance strain gauge sensor
- 3 Hundred thousand ISN precision
- Can distinguish 0.3d unit weight
- Multiple unit options
- Reaction speed adjustable
- LCD display with direct indication of symbol
- Display the battery charge level after power-on
- Self-protection as power shortage
- Preset the upper and lower limit alarm and the known,
- Dynamic detection and optional zero tracking
- Filtering function with vibration and shake elimination²
- Highly resistant to interference, no loss of data due to incorrect operation and automatic program repeatability
- Optional function of linking external alarm lamps (upper and lower limits) or automatic dosing equipment
- Optional RS232 or RS232 printer interface
- Optional: external alarm light; RS232, Bluetooth interface; Printer, PLC

HIGH-DEFINITION LARGE SCREEN READING CLEAR

High definition energy-saving super large display

MORE ACCURATE COUNTING

Automatic averaging function, that is, the weight of the counted standard parts is automatically averaged.

Can automatically average each weight of the product

MULTIPLE USAGE SCENARIOS




Hardware counting

Automatically calculate product quantity



Jewelry craft

High precision, small error



Factory warehouse

ABS material is durable and fall resistant



Drugstore herbs

Accuracy up to 0.01g

TECHNICAL PARAMETER

MODEL	ED-1.5C	ED-3C	ED-6C	ED-15C	ED-30C
Capacity	1.5KG	3KG	6KG	15KG	30KG
Resolution	0.05G	0.1G	0.2G	0.5G	1G
Display	LCD Display				
Voltage	AC220V Battery6V4AH				
Packing Box	370x330x140mm				

STANDARD CONFIGURATION



PCS



SUM



UNIT



TOL



BATTERY

FACTORY SELECTION



RS232

CAS

CAS BLDG., # 440-1, SUNGNAE-DONG,
GANGDONG-GU, SEOUL, KOREA

TEL_ 82 2 2225 3500

FAX_ 82 2 475 4668

<http://www.globalcas.com>

Specifications are subject to change for improvement without prior notice.

ED-C

Unit:mm

