

ESW *IP68*

Waterproof Weighing Scale



FEATURES

IP68 CERTIFIED BY SGS

- ◆ Sealed waterproof silica gel strip blocks water from infiltrating into the scale.
- ◆ Surrounded by waterproof grade sheeting to ensure the water free.
- ◆ 1/3,000~1/6,000 display resolution available.
- ◆ Aluminum frames coated with anti-corrosion treatment for longer lifespan.
- ◆ LCD or LED display selectable.
- ◆ Stainless steel made for anti-rust.
- ◆ High speed of 24bits AD fast reacts and shortens the weighing operation duration.
- ◆ Selectable units: Kilogram (kg), gram (g), ounce (oz), and pound (lb) weighing units available.
- ◆ Built-in rechargeable battery can be easily replaced.
- ◆ Low power indication and auto power off.
- ◆ Well-designed protection point for transportation.
- ◆ Concave handle for easy carrying.

IP68



OPTION

- ◆ Dual display: 29x90mm; 6 digits, 15mm height (only for LED model)

SPECIFICATION

MODEL	CAPACITY	DIVISION	RESOLUTION
ESW-3	3kg	0.5g	1/6,000
		1g	1/3,000
ESW-6	6kg	1g	1/6,000
		2g	1/3,000
ESW-15	15kg	2g	1/7,500
		5g	1/3,000
ESW-30	30Kg	5g	1/6,000
		10g	1/3,000

Operating Temperature: Non-approval model: 0°C ~ 40°C (32°F ~ 104°F)
Approval model: -10°C ~ 40°C (14°F ~ 104°F)

LCD Display: 35x108mm; 6 digits, 25mm (height), LED backlight

LED Display: 35x108mm; 6 digits, 15mm (height); dual display optional

Power Source: AC 110V~240V (±10%) adapter+ DC 6V / 4Ah rechargeable battery

Dimensions: 240 x 117 x 280 mm (W x H x D)

Weight of the scale: Around 3.5kg



EXCELL PRECISION CO., LTD.

6F., No.127, Ln. 235, Baoqiao Rd., Xindian Dist., New Taipei City 231, Taiwan

Tel +886 2 8919 1000 Website www.excell-scale.com

Fax +886 2 8919 1177 E-mail sales@excell-scale.com