



Electronic Floor Scale



Showned with optional ramps

UNIQUE FEATURES:

- Diamond tread-plate safety deck
- 4 NTEP, OIML R60 approved shear beam load cell
- Factory Mutual approved load cells
- Reinforced high strength construction
- Signal trim summing board
- Rigid structure steel channel frame
- RS232C serial port is standard accessory (except FB530)
- Steel ball bearings adjustable foot assemblies leveling uneven floor

20i



DL600S



DL500s



CI201A



R320



QW



FB530



Specifications:

MODEL	DL600s-1200K DL500s-1200K QW-1200K FB530-1200K	DL600s-2500K DL500s-2500K QW-2500K FB530-2500K	DL600s-2000KL DL500s-2000KL QW-2000KL FB530-2000KL	DL600s-5000K DL500s-5000K QW-5000K FB530-5000K
Capacity	1200 Kg	2500 Kg	2500 Kg	5000 Kg
Resolution	0.2 Kg	0.5 Kg	0.5 Kg	1 Kg
Platform Size	1200 x 1200 mm		1500 x 1500 mm	1500 x 1500 mm
Linearity	+/- 2 division			
Display	VFD (DL600s) ; LED (DL500s) ; LCD (QW, FB530)			
Operating Temperature	-10°C ~ 40°C / 14° ~ 104°F			
Enclosure (Indicator)	Stainless steel (DL600s, DL500s, QW) ; ABS (FB530)			
Power	220VAC 50/60Hz			

MODEL	20i-1200K R320-1200K CI201A-1200K	20i-2500K R320-2500K CI201A-2500K	20i-2500KL R320-2500KL CI201A-2500KL	20i-3000K R320-3000K CI201A-3000K
Capacity	1200 Kg	2500 Kg	2500 Kg	3000 Kg
Resolution	0.2 Kg	0.5 Kg	0.5 Kg	0.5 Kg
Platform Size	1200 x 1200 mm		1500 x 1500 mm	1200 x 1200 mm
Linearity	+/- 2 divisions			
Display	6-digit weight display, 0.8”(20mm) height LED enunciators for operational status LED Backlit LCD with six 20mm high digits with units and annunciators LED Backlit LCD with six 25mm high digits			
Operating Temperature	-10°C ~ 40°C / 14° ~ 104°F			
Enclosure (Indicator)	IP67 stainless steel washdown (20i); ABS (R320, CI201A)			
Power	Auto-switching, ACD power 115-230VAC (20i) 6 x AA batteries or AC/DC adaptor (R320) ; AC/DC adaptor (CI201A)			

MODEL	20i-3000KL R320-3000L CI201A-3000KL	20i-5000K R320-5000K CI201A-5000K	20i-10000K R320-10000K CI201A-10000K	20i-10000KL R320-10000KL CI201A-10000KL
Capacity	3000 Kg	5000 Kg	10000 Kg	10000 Kg
Resolution	0.5 Kg	1 Kg	2 Kg	2 Kg
Platform Size	1500 x 1500 mm	1500 x 1500 mm	1500 x 1500 mm	1500 x 2000 mm
Linearity	+/- 2 divisions			
Display	6-digit weight display, 0.8”(20mm) height LED enunciators for operational status LED Backlit LCD with six 20mm high digits with units and annunciators LED Backlit LCD with six 25mm high digits			
Operating Temperature	-10°C ~ 40°C / 14° ~ 104°F			
Enclosure (Indicator)	IP67 stainless steel washdown (20i); ABS (R320, CI201A)			
Power	Auto-switching, ACD power 115-230VAC (20i) 6 x AA batteries or AC/DC adaptor (R320) ; AC/DC adaptor (CI201A)			

Specifications subject to change for improvement without notice

For other platform sizes and capacities, please consult the factory. All stainless steel structure and load cells (IP68) available.

Options: Scale printer, Label printer, Remote display, Low angle ramp



Weightronic Technology Ltd.

G/F., 34 Nam Cheong Street, Sham Shui Po, Kln., Hong Kong

Tel: (852) 2381 8818 Fax: (852) 2391 9919

Email: sales@weightronic.com <http://www.weightronic.com> <http://www.磅.hk>