
"WWSD" WHEEL WEIGHING PLATFORMS



WWSD platform.



WWSD: dimensions in mm.



Platforms designed for creating weighing stations for large sized vehicles fitted with twinned wheels or large sized tyres (articulated lorries, tractor-trailers, building yard vehicles, etc.); fitted with integrated wheels for easing the transport. Particularly suitable for dynamic weighing.

FEATURES

- Platform dimensions: 900x611mm. Height 58mm. Weight approximately 41,5kg.
- Loading surface: 900x500mm.
- Fitted with wheels for transporting the platform.
- Sturdy structure, made in special aluminium, which guarantees lightness and makes these suiable also for harsh working conditions.
- Cable with quick connector, platform side.
- 10 m cable for connecting platform to indicator, complete of connectors.
- IP68 stainless steel load cells.
- Hermetic junction box with IP68 protection degree.
- Special vulcanised nonslip rubber applied under the platform for good grip on all surfaces.
- Extremely simple and reliable connection of the scale to the weight indicator.
- Fitted with IP68 protection, with IP68 connector and PUR cable.
- The WWS platforms are patented; the number is 1.342.302.
- Available also in CE-M APPROVED version.

OPTIONS AND ACCESSORIES

- High resolution model for internal factory use. Frame for flush floor installation.
- Levelling module for axle weighing.
- On/off ramp.

NOTES ON THE CE-M APPROVED VERSIONS

- The platforms are for legal for trade use:
 - In the **single-platform systems**, not used to weigh vehicles.
 - In the **wheel weighing systems** (with Dini Argeo indicator) in which the number of platforms is equal to the number of vehicle wheels. The weight of the single platform as well as the vehicle total weight are legal for trade use, since these are obtained with a single weigh.
- **NOTE**: In the axle weighing systems with 2 WWS platforms, the weight is for internal use only.

Available versions	6				
	Surface	Max	d	CE-M	d* HR
Code	l x w (mm)	(kg)	(kg)	3000e (kg)	(kg)
WWSD6T	900x500	6000	2		0,2
WWSD10T	900x500	10000	5		0,5
WWSD15T	900x500	15000	5		0,5
WWSD20T	900×500	20000	10		1
WWSD6TM M	900x500	6000		2	
WWSD10TM M	900x500	10000		5	
WWSD15TM M	900x500	15000		5	
WWSD20TM M	900x500	20000		10	

NOTES:

- The CE-M division is referred to the weight of the single platform.
- The CE-M division in which the sum weight is indicated in the wheels weighing systems (4 platforms) is equal to the sum of the single platforms' divisions, rounded. Example: with 4 approved platforms with division 200g, the approved sum weight will be indicated with division 1kg.

Options only available at time of order

Code	Description
EHR	High resolution model for internal factory use.

Accessories

Code	Description
CBWWSIP	10m connection cable between WWS platform and weight indicator in transport case (as a spare part).
WWSDTF	Frame for flush floor installation for WWSD series platform.
WWSDLM	Levelling module for axle weighing with WWSD series' platforms, surface 1200x700mm, h=52mm, weight
	of about 28 kg, fitted with junction and fixing kit.
WWSDLMR	Wooden on/off ramp with a metal protective coating, 700x760mm dimensions, for WWSD platforms.

Main connectable indicators

Code	Descri	ption			
DFWKRP	Weight indicator in Rack version with specific programme for vehicle weighing, with transport case, 17-				
	key key	ypad, backlit display, time	date and attached therm	nal printer.	
3590EKR03P	Weight indicator in the "AF03" version for vehicle weighing systems, with printer, transport case, 25-key			transport case, 25-key	
	keypad	, LED display and backlit	graphic LCD display.		
3590EKR08P	Weight	Weight indicator in the "AF08" version for wheel weighing systems or axle weighing systems, with printer,			
	transport case, 25-key keypad, LED display and backlit graphic LCD display.				
3590EKR09P	Weight indicator in the "AF09" version for dynamic or static axle weighing systems, with printer, transport				
case, 25-key keypad, LED display and backlit graphic LCD display.					
Available indic	ators	DFWKRP	3590EKR03	3590EKR08	3590EKR09

		Freely Programmable	Freely Programmable	Freely Programable
Specifications	>> Technical data sheet	>> Technical data sheet	>> Technical data sheet	>> Technical data sheet
Functions	- Wheels weighing - Axles weighing - In/Out (without memory) - Calculating the barycentre	- Vehicles weighing - In/Out (with memory)	- Wheels weighing - Axles weighing - Calculating the barycentre	- Static axles weighing - Dynamic axles weighing - In/Out (with memory)
Max. reading channels	4	2	4	1
Max. Platforms	4 (up to 8, 2 per channels)	8 (equalized)	4 (up to 8, 2 per channels)	2 (equalized)
Visualization	Single channelCombination of channelsTotal weight	- Total weight	Single channelsSingle axlesTotal weightBarycentre	- Single axles - Total weight
Printout	 Headers Single channels Combination of channels Total weight Difference In/Out Barycentre 	Completely programmable	Completely programmable	Completely programmable
Databases	-	- Customers - Vehicles - Materials	- Data	- Customers - Vehicles - Materials
Approval	- Weight of the single platform - Total weight (only in the wheels weighing)	- Total weight	- Weight of the single platform - Total weight (only in the wheels weighing)	-

